

EC-100-LSXT+-1000

SXGA+ 100-INCH DLP® REAR-PROJECTION CUBE WITH CLUSTER-LED PROJECTION TECHNOLOGY



) PRODUCT DESCRIPTION

The eyevis **EC-100-LSXT+-1000** is a modular rear-projection cube with a **screen diagonal of 100 inch** (ca. 254 cm) and **SXGA+ resolution (1400 x 1050 pixels)**. The EC-100-LSXT+-1000 uses innovative Cluster-LED technology for illumination. EC-100-LSXT+-1000 is a revolutionary development by eyevis and manufactured in Germany. It is especially designed for applications which require a reliable 24/7 operation. Thanks to Cluster LEDs with a higher light output we are able to provide the EC-1000 series of our rear-projection cubes with enhanced brightness level.

Through the enhanced brightness levels of the EC-1000 series the new cubes can now also be installed in applications that require brighter image representation, e.g. in presentation areas or broadcast studios. For most other installation, for example in control rooms, the performance of the LEDs can be reduced to lower levels, which results in less power consumption and thermal load. In addition, the reduced power of the LEDs further extends their life-time. The cubes from the EC-1000 Series are available in XGA, SXGA, SXGA+, UXGA, Full HD and WUXGA.

The Cluster-LEDs used as light source for the EC-1000 series have an active LED surface divided into several sections. Besides higher light output this also guarantees that in the event of a failure of a single LED section, the image is preserved in almost its entire condition. Of course, all optional features that make our rear-projection units so flexible to use are also available for the EC-1000 Series. This includes the various available screens, different basement options, optimization features for installations in broadcast areas, or the automatic colour/brightness adjustment system for cube walls (ACT).

) THE ADVANTAGES AT A GLANCE

DURABILITY

- Durable and constant picture quality on all Cubes
- Modular, highly available display concept for 24/7 operation
- Low service and maintenance costs

COLOUR-RESCUE-CONTROL

- Special operation mode to compensate defect LED modules
- Image remains visible even with one or two defective LEDs
- Colour replacement according to the customer's image content

OUTSTANDING IMAGE QUALITY


- High contrast and best brightness
- Colour uniformity and wide viewing angle
- Best visibility in any lighting condition

) ECO-FRIENDLY CONCEPT




HEATPIPE COOLING SYSTEM

As with all other eyevis LED cubes, the EC-1000 Series continues to rely on our innovative heatpipe cooling system, which has proven its reliable and highly effective function in thousands of cubes in diverse operating conditions. In addition to that, our heatpipes require absolutely no servicing and contain no toxic liquids.



LOW POWER CONSUMPTION

Although the cubes from the EC-1000 Series have a higher light output, power consumption has not risen. For typical applications like in control rooms, the power consumption is even up to 20% less compared to values of our standard cubes. At the same time the heat dissipation of the cubes could be lowered, which reduces the demands on the HVAC systems in control rooms. Thus, the devices from the EC-1000 Series are not only brighter, they also save energy.



INTEGRATED OPTIMISING OPTIONS

- Perfect system adjustment with eyeDevice Setup software
- Fast and easy parameter setting
- Optional Multi-Cube Auto-Colour-Tracking

PRECISION SCREEN CONCEPT

- Different screen options available to suit any requirements
- Minimum gaps between cubes thanks to clipping method
- Very easy and fast installation

AVAILABILITY AND RELIABILITY

- Extremely long lifetime of the LED lights
- Qualitative high value components
- Highly efficient maintenance-free heatpipe cooling



EC-100-LSXT+-1000

SXGA+ 100-INCH DLP® REAR-PROJECTION CUBE WITH CLUSTER-LED PROJECTION TECHNOLOGY



TECHNICAL SPECIFICATIONS

Type:	EC-100-LSXT+-1000, eyevisCube 100" with Cluster-LED illumination and native SXGA+ resolution		
Description:	Digital 100 inch DLP®-rear-projection unit for data and video representation		
Resolution:	1400 × 1050 Pixel (SXGA+/4:3) / Chip: DMD-Chip SXGA+ / LVDS 0.95"		
Brightness*:	HB Screen Scheibe: 230 cd/m ² (max. / Full Brightness Mode) / 198 cd/m ² (typ. / Normal Operation Mode) Beta Screen Scheibe: 125 cd/m ² (max. / Full Brightness Mode) / 107 cd/m ² (typ. / Normal Operation Mode)		
Contrast Ratio:	1500:1 (typ. / static contrast)		
Brightness Uniformity:	≥95% (SUR25)		
Image Size (WxH):	2000 × 1500 mm (ca. 100 inch / ca. 254 cm screen diagonal)		
Dimensions (WxHxD):	2000 × 1628 × 1350 mm		
Weight:	ca. 160 kg (incl. housing, projection engine, input box & screen)		
Input:	1× DVI-D, optional with Scaler Board: 2× RGB, 2× DVI, 2× Composite Video, 1× Y/C, 1× YUV, 1× S-Video		
Projection Screen:	High Brightness Screen, Beta Screen		
Frame:	0.3 mm		
Power Consumption*:	Full Brightness Mode:	235 W	
	Normal Operation Mode:	160 W	
	Reduced Power Mode:	120 W	
Heat Dissipation:	545 BTU/h (@Normal Operation Mode)		
Median LED Lifetime:	>60,000 hrs under normal environmental conditions / L70B50 manufacturer information) (75,000 - 90,000 hrs in 'Low Power Operation Mode', i.e. additional 15,000 to 30,000 hrs depending on the amount of power reduction)		
Software:	eyeDevice Setup Software		

ENVIRONMENTAL

Temperature Conditions:	10-40° C / recommended 15 - 25 °C / for Seamless Screens 18 - 25 °C / Storage: 0 - 50 °C
Humidity:	0% - 80 % not condensing
Altitude:	0 - 3000 m
Noise Level:	≤ 36 dB

ORDERING INFORMATION

Item Numbers:	19040 -> EC-100-LSXT+-BS-1000 (100" DLP® Cube with SXGA+ resolution and BetaScreen rear-projection screen)
---------------	---

OPTIONS

<ul style="list-style-type: none"> ▪ Different screen versions to suit the requirements of different fields of application (viewing angles, brightness uniformity, etc.) ▪ Scaler Board (internal split controller up to 10x10 Matrix, with 2x DVI, 2x RGB, 2x Video) ▪ ACT - Auto-Colour Tracking, auto-adjustment of brightness and colours for each display according to the adjusted values ▪ EYE-MSP - Matrix-Shading-Processor integrated in cube ▪ EYE-MDP - Matrix and Delay Processor integrated in cube ▪ EYE-SCP - Shading and Colour Processor integrated in cube ▪ EC-MAS - Motorized geometry adjustment via IR remote control or PS2 ▪ Network Board ▪ Service and Maintenance Contracts ▪ Different Basement Options: Standard Basement, Basements on Wheels, Basements on Rails, Anti-Vibration Basements
--

* Full Brightness Mode -> full LED brightness with calibrated colours / Normal Operation Mode -> approx. 70% of LED brightness with calibrated colours



eyevis GmbH

Hundsschleestrass 23 • 72766 Reutlingen • Germany

Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22

www.eyevis.de • info@eyevis.de

As at: 10.10.2014/V1.3 • Subject to change!

All trademarks and registered trademarks are the property of their respective owners. Copyright © 2014 eyevis GmbH. All rights reserved.